

MULTIFUNCTION BLAST-CHILLER SHOCK-FREEZER THEONE H505TS

TECHNICAL FEATURES:

- External sides and top in AISI 304 stainless steel th. 0.6 mm (Scotch-Brite satin)
- Door in stainless steel AISI 304 th. 0.8 mm (Scotch-Brite satin)
- Internal compartment with rounded corners in AISI 304 stainless steel
- Cavity with central drain for discharge of washing water
- High-density polyurethane insulation (about 42 kg/m³), thickness 60mm, without HCFC
- Anti-condensation heating element, placed under the frame
- Ergonomic handle on the complete door length and magnetic gaskets on the 4 sides of the door
- Patented humidity injection system

5 FUNCTIONS

- Blast Chilling
- Shock Freezing
- Thawing at controlled temperature and humidity
- Proofing retarder
- Low temperature cooking

INTERNAL SETUP:

- Removable guides in stainless steel AISI 304, Easily repositioned to accommodate GN1/1 or 600x400 trays
- Removable "L" guides in AISI 304 stainless steel, which can be positioned interlocking every 15 mm
- Heated core probe, with 4 measuring points

COOLING SYSTEM:

- Indirect airflow
- Hermetic compressor (semi-hermetic in mod. H524TS)
- R452a refrigerant
- High performance Copper-aluminium evaporator with cataphoresis anti-corrosion treatment
- High performance copper-aluminium condenser
- Patented hot gas defrosting system for the evaporator
- Automatic system evaporating the frost melted off the evaporator, without using electricity (heating cartridge on mod H524TS)

CONTROLS AND SAFETY DEVICES:

- 7 " IPS capacitive TOUCH display in high definition placed on the door, easy to use
- Circuit breaker for compressor protection
- USB port for download cycles, firmware upgrade, upload / download of recipes, etc.
- Internal fan stop by micro switch when door is opened

OPTIONS / ACCESSORIES:

- Version prepared for remote group
- Version with water condensation



Technical features:



Blast Chilling and Shock Freezing



Low temperature Cooking up to 85°C




Thawing at controlled humidity and temperature



Proving retarder



Water inlet




Trayholders can be positioned for EN-GN




Stainless steel construction



Evaporator in cataphoresis



Magnetic door gasket removable w/o tools



Rounded corners



Heated core probe w 4 measuring points



Hot gas defrosting


MULTIFUNCTION BLAST-CHILLER SHOCK-FREEZER THEONE H505TS

SCHEDA TECNICA	H 505TS
Temperature	"Hot cycles, blast chilling and shock freezing
Dimensions (LxPxH) mm	790x720x850
Door opening (WxH) mm	670x380
Internal depth mm	410
Insulation thickness mm	60
YIELD EN17032 BLAST-CHILLING kg/ciclo	20
YIELD EN17032 SHOCK-FREEZING kg/ciclo	13
ELECTRICAL CONSUMPTION EN17032 Blast Chilling kW/Kg	0.070000000000000001
ELECTRICAL CONSUMPTION EN17032 Shock Freezing kW/Kg	0.25
Measure pan	600x400
Totale	5
Pitch mm	60
Capacity gelato tubs 160x360h120 n°	6
Capacity gelato tubs 250x360h120 n°	4
Refrigerant gas	R452A
Gas quantity w air cooling g	1000
Compressor Hp	1
Noise level dB(A)	< 70
COOLING POWER EN12900 W	1430 @ Tevap=-10°C Tcond=+40°C
Climatic class	5 (ex T)
Power supply V/~/Hz	230/1/50
Max power consumption W	1117
Max absorbed current A	5.5
Defrosting	Gas caldo
Max power consumption heating W	625
Max absorbed current in heating A	2.7
Heating power W	500
Packing dimensions, standard (WxDxH) mm	850x780x1005
Packing volume m³	0.66
Net weight kg	86
Gross weight in std package kg	101

HIBER Ali Group S.r.l.

Via Cavalieri di Vittorio Veneto, 25 - 32036 Sedico (BL) - IT
Tel.+39 0437 1849201 Fax +39 0437 1849290
<http://www.hiber.it> E-Mail: info@hiber.it

MULTIFUNCTION BLAST-CHILLER SHOCK-FREEZER THEONE H505TS



Ⓔ CONNESSIONE ELETTRICA
ELECTICAL CONNECTION

Ⓕ INGRESSO H2O
H2O INLET

Ⓖ SCARICO H2O
DRAIN CONNECTION

DIMENSIONI mm
DIMENSIONS [in]

HIBER Ali Group S.r.l.

Via Cavalieri di Vittorio Veneto, 25 - 32036 Sedico (BL) - IT
Tel. +39 0437 1849201 Fax +39 0437 1849290
<http://www.hiber.it> E-Mail: info@hiber.it