

HIELO H323

BLASTCHILLERS

Counter top 3 GN 2/3

FUNCTIONS:

Blast chilling cycles +3° HARD/SOFT,

Shock freezing cycles -18° HARD,

Blast chilling yield (+3°C)/Kg **8**

Shock freezing yield (-18°C)/Kg **5**

Climatic class **5**

Forced ventilation

TECHNICAL DATA

Net width (mm) **600**

Net depth (mm) **605**

Net height (mm) **400**

Net weight (Kg) **45**

Distance between grids (mm) **70**

Electrical power **230/1/50**

Elec. Power** (W) **700**

Max absorbed current (A)** **4,3**

Cooling power (W) **407**

compressor (HP) **1/3**

NOISE LEVEL [dB(A)] **< 70**

Freon (Gas) **R452a**

Gross weight (Kg) **51**

Shipment data (WxDxH) mm **630 x 880 x 500**

MAIN FEATURES

monocoque construction •

Internal and external construction in AISI 304 18/10 stainless steel •



Capacity GN 2/3 •

Finely "Scotch Brite" satined exterior •

PU insulation free from CFC and HCFC, density 42 kg/m3 •

Magnetic seals on 4 sides •

Removable basket, for rack support, that can be extracted with no need to use tools for easier cleaning •

GRIDS

3 inox grids GN 2/3

CONTROL INTERFACE

